

REFRIGERATED CENTRIFUGE VFC-22K



Refrigerated Centrifuge



VFC-22K

Super-Large Capacity Low Speed Refrigerated Centrifuge

VFC-22K super-large capacity refrigerated centrifuge, a new and smart centrifuge, which is jointly developed by the well-known centrifuge manufacturer and national key university. It has passed the MCA test and rotor service life test by authority agency in the United States. Max capacity up to 8x2200ml, it is the preferred product in the fields of blood bank, pharmacy and biological products.

Carbon Fiber Rotor

The carbon fiber rotor, passed 100,000 times life service test in 2017, features light weight, chemical corrosion resistance, high mechanical strength, long service life, large capacity as well as high speed (Max speed 9000rpm with 6x1000ml angle rotor), providing high efficient and perfect product for bio-pharmacy, biological products, chemical industry etc.



Product advantages

♦Automatic door locking system (optional)

The centrifuge door can be opened or closed by a single soft touch of a button. Door lid come with intelligent anti pinch device.

♦Automatic suction device of centrifuging windshield (optional)

The windshield is sucked to the door lid when opened without labor intervention prevent it from falling down.

♦Safe Structure

The overall unit has passed MCA (Maximum Credible Accident test),

After MCA is generated, the centrifuge door lid shall not be opened, and no solid greater than 0.5mm shall blown out of the centrifuge chamber, the position movement shall not exceed 30cm, ensure the personal safety of instrument operator to the greatest extent. (MCA test video can be provided)

♦Reliable Material

Centrifuge chamber adopt 2mm thick 316L stainless steel, Housing (3mm Q235 steel), Containment (22mm Q235 steel), Diaphragm in door lid (2.5mm Q235 steel)

♦Energy saving

Dynamic compressor control (DCC) technology for optimized cooling performance. When the door lid is opened, the compressor is closed or the sleep time can be set to save energy. Rotor with windshield, little friction and generates little heat.

♦Super-large Capacity

It can process sample with the capacity of 8x2200ml, 6x2400ml, separating max 17.6L sample in one cycle, which greatly improves the production efficiency.



◆Built-in safety

Featuring multiple protection , Such as automatic rotor identification, imbalance protection, over-speed protection, over-temperature protection, motor overheating protection, door lid protection and so on.

◆Extensible

The system adopts unified and standard Ethernet communication interface and provides key parameter point table , to facilitate system expansion and bring data into system monitoring.

◆Programmable

Save up to 3000 user-defined program. Users can name each program to distinguish it. Each program can be divided into 5 steps (set speed, time, temperature), to meet the diversified experimental needs.

◆ACC/DEC Rates

Featuring 10 acceleration and 11 deceleration rates, to prevent the sample from second emulsion or turbid, and achieve best centrifuging result.

◆Main interface function

In manual mode, the centrifuge parameters can be set quickly, and the G-force and speed can be switched by soft touch the key. For the online monitoring of temperature and speed, the stability of temperature and speed during spinning can be viewed through the curve.

◆Powerful System Setting Function

Running data , error code record and operation record can be stored through the system setting. Chinese / English operation language optional. And user authority management and other characteristic functions can be managed as well.

◆Centrifuge Management System(Optional)

It can monitor 1 to 100 centrifuges through intelligent terminal (computer), monitor the operation status of centrifuges, and save relevant records of centrifuge operation, Establish a safe connection with the centrifuge and remotely control the startup and stopping of the centrifuge.



Technical parameter

Order NO	0204258000			
Max Speed	Angle Rotor	9000r/min	Swing Rotor	4500r/min
Max RCF	Angle Rotor	18610xg	Swing Rotor	6756xg
Max Capacity	Angle Rotor	6x1000ml	Swing Rotor	8x2200ml
Time Setting Range	two mode 1min-99h59min ,1s-99min59s optional, default mode 1min-99h59min			
Timing mode	Start Timing after Spinning, Start Timing after Reach Setting Speed, Continuous Timing, Operation at an appointed Time			
Temperature Setting Range	-20°C~40°C, Setp 1°C ajustable, The fast pre-cooling temerature can reach -20°C			
Sample Temperature Accuracy	Ensure sample (liquid) temperature accuracy controlled to ±1°C			
Temperature Accuracy	±2°C			
Speed Accuracy	±10r/min			
Power Supply	AC220±22V 50Hz			
Power Consumption	7.5kW			
Noise	≤70dB (A)			
Rotor Identification	Yes			
Imbalance Protection	Yes			
Pre-cooling function	Yes			
Computer Control	RS485 or RS232			
Protection Function	Imbalance Protection,Rotor-identification,Door Lid Anti Pinch Protection,Motor Overheating Protection,Over-Speed Protection,Over-temperature Protection			
Dimension (WxDxH)	875×996×1000 (mm)			
Packing Dimension (WxDxH)	1080×1310×1340 (mm)			
Net Weigh	575kg			





Rotor parameters

No:1



Rotor Type: Angle rotor
Max Speed: 8000r/min
Max RCF: 14472xg
Max Capacity: 6x1000ml
Order NO: 0301080100
Adapter: 24x50ml (conical/round) 、
6x250/500ml

No:5



Rotor Type: Angle rotor (Carbon Fibre)
Max Speed: 9000r/min
Max RCF: 18610xg
Max Capacity: 6x1000ml
Order NO: 0301080120
Adapter: 24x50ml (conical/round) 、
6x250/500ml

No:2



Rotor Type: Swing Rotor
Max Speed: 4500r/min
Max RCF: 6756xg
Max Capacity: 6x2400ml
Order NO: 0302080200
(rotor, bucket and windshield
included)



Rectangular Bucket
Max RCF: 6756xg
Max Capacity: 6x2400ml
Order NO: 0303891024



Bottle
Max Capacity: 6x2400ml
Order NO: 0305536210

No:3



Rotor Type: Swing Rotor
Max Speed: 4500r/min
Max RCF: 6315xg
Max Capacity: 6x2x1000ml
Order NO: 0302080300
(rotor, bucket and windshield
included)



Bucket
Max RCF: 6315xg
Max Capacity: 6x2x1000ml
Order NO: 0303891019



Bottle
Max Capacity: 6x2x1000ml
Order NO: 0305536160

No:4



Rotor Type: Swing Rotor
Max Speed: 4500r/min
Max RCF: 6756xg
Max Capacity: 6x2x500ml
Order NO: 0302891105



Bucket
Order NO: 0309891054



Blood bag adapter
Order NO: 0304891425
Max Capacity: 6x2x500ml
or 24x200ml



VITANIX

future
of
healthcare



+38664150661 | INFO@VITANIX.SI | WWW.VITANIX.SI

ADDRESS: Linhartov podhod 67, 1000 Ljubljana, Slovenia
Trg, Franca Fakina 17, 1420 Trbovlje Slovenia

VITANIX D.o.o reserves the right to make any changes to the information, including specifications, without notice

